



TDS of BLUERAY Revolution

Products Intro :

- 1.Products are mainly made of resin, pigments, filler and additives.
- 2.This product has excellent printing fitness, curing speed, bright color, high saturation, suitable for Common paper, suitable for high-speed printing machine.

	Fluidity	TACK	DRY(s)	FINENESS	STRENGTH
M	36 (36-41)	10.5 (9-11)	96 (70-120)	10 (0-13)	100
Y	36 (36-41)	10.2 (9-11)	76 (70-120)	10 (0-13)	100
C	37 (36-41)	10.5 (9-11)	76 (70-120)	10 (0-13)	100
K	37 (37-39)	11 (10-12)	96 (70-120)	12.5 (0-13)	100

Remark:

Tack : Rheumator (water temperature: 38 degrees, 400rpm, 1min)

Fluidity : Parallel plate viscosimeter (Room temperature: 25 degrees, enlarged diameter after 1min)

Main Character :

1. Substrate Adaptability Wide: suitable for coated paper,
2. Good printing suitability, good transfer, stabilization printing performance
3. Good ink-water balance.
4. The expansibility of ink rollers and blanket is low, which is conducive to the service life of these materials.

User Guide :

Printing Materials :

Plate : Such as the use of offset printing, built to use ink PS version;
InkRoller : Suggest to use ink rubber roller.
Blanket : Suggest to use ink blanket
Fountain Solution : Can use the general foundation solution

Packing & Storage :

1. Packaging and Specifications: (Vacuum iron can, net weight 2.5 kg x 8)
2. Shelf life: 24 months with good storage.

Announcements :

1. Ink Storage: ink should be keep in a light-avoiding, cool environment, temperature $\leq 25^{\circ}\text{C}$.